

## Rigid PVC Pressure Pipes and Fittings

*... The most comprehensive range with a wide spectrum of fittings*



IS:4985-2000



CML 1235335

The Supreme Industries Ltd. is an acknowledged leader of India's plastic industry. It is credited with pioneering several path breaking products and has gained a valuable experience in providing innovative and cost effective piping solutions. The Company has been a trend setter and a torch bearer in the transition from conventional to advanced plastic piping products in the country. The Company's objective is to meet the growing needs of its clientele in water and waste management and in infrastructure sector through a specially designed high performance range of piping products. The innovative product portfolio offered by Supreme is extensive in nature and applications. With its range of over 7500 products, the most comprehensive in the piping industry, Supreme caters to almost every conceivable need and application in piping.

Supreme uPVC pressure piping system with a wide spectrum of pipes and fittings in different sizes and pressure classes is an ideal solution for water supply and irrigation. Supreme pressure piping system has become the prime choice of farmers, water supply bodies and different government institutions who have successfully replaced the conventional piping with our products.



## The System

Supreme offers an exhaustive range of uPVC pressure pipes and fittings. Pressure pipes are manufactured as per IS 4985:2000 standards and are available in 20 to 450 mm sizes in different pressure classes. Pipes with both types of joints, i.e., solvent cement type and rubber seal type are available. Varieties of moulded fittings and wide range of handmade fittings are also available. Moulded fittings are manufactured as per IS 7834 and fabricated fittings are manufactured as per IS 10124 and company standards. These pipes and fittings are used for a variety of applications like, irrigation, water supply, industrial process lines, swimming pools, firefighting mains, etc. These pipes are superior to CI, DI or RCC pipes in terms of being light in weight, easier and quicker installation, excellent corrosion and chemical resistance properties, high flow rates, long life and economy. These pipes have the approval of M.J.P.

## Features and Benefits:

**Odorless and hygienic** - These pipes are an excellent choice for carrying potable water as they do not allow contamination.

**High corrosion resistance** - Being immune to chemical, electrolytic and galvanic action, these pipes are free from corrosion which ensures a much longer and useful life.

**High chemical resistance** - Pipes offer excellent resistance to acids, oxidizing agents, alkalis, oils and domestic effluents.

**Smooth bore** - Pipes have a mirror smooth inside surface offering much better flow characteristics in comparison to AC, CI and GI pipes.

**Self extinguishing quality** - This feature eliminates the need

for fire resistant coatings.

**Maintenance free** - Corrosion resistant property of the PVC pipes eliminates the need for repeated painting or coating like in the case of GI pipes.

**Long lasting** - As these pipes are free from weaknesses caused by scale formation, rusting, weathering and chemical action, they have a much longer effective life.

**Economical** - Despite being superior to conventional pipes, Supreme PVC pipes are very light in weight and last much longer than older piping systems offering a great economy in handling, transportation, installation and replacement.

## Salient Features:

- General dimensions conform to IS 7834-87.
- Wall thickness is designed to meet required working pressure.
- Close to dimensional tolerance.
- Different working pressure ratings upto 16 kgf/cm<sup>2</sup> for different sizes


## Properties:

- Hazen Williams constant : 150 (remains constant)
- Specific gravity : 1.41-1.46
- Coefficient of linear expansion :  $5.4 \times 10^{-5}$  mm/m/°C
- Combined flexural and compressive strength : 600-650 kgf/cm<sup>2</sup>
- Impact strength at 20°C : 3 Kgf/cm<sup>2</sup>
- Modulus of elasticity :  $3-3.8 \times 10^4$  Kgf/cm<sup>2</sup>
- Vicat softening point : 80°C
- Electrical resistance :  $10^{14}$  ohm-cm

Dimensions of uPVC Pressure Pipes as per : IS 4985:2000


Nominal Outside Diameter (mm)	Tolerance on Outside Diameter	Wall Thickness (mm)													
		Class 1 (PN) 2.5 kgf/cm <sup>2</sup>		Class 2 (PN) 4 kgf/cm <sup>2</sup>		Class 3 (PN) 6 kgf/cm <sup>2</sup>		Class 4 (PN) 8 kgf/cm <sup>2</sup>		Class 5 (PN) 10 kgf/cm <sup>2</sup>		Class 6 (PN) 12.5 kgf/cm <sup>2</sup>		Plumbing Pipes	
		Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max
20	+ 0.3	-	-	-	-	-	-	-	-	1.1	1.5	1.4	1.8	2.8	3.3
25	+ 0.3	-	-	-	-	-	-	1.2	1.6	1.4	1.8	1.7	2.1	2.9	3.4
32	+ 0.3	-	-	-	-	-	-	1.5	1.9	1.8	2.2	2.2	2.7	3.4	3.9
40	+ 0.3	-	-	-	-	1.4	1.8	1.8	2.2	2.2	2.7	2.8	3.3	3.6	4.2
50	+ 0.3	-	-	-	-	1.7	2.1	2.3	2.8	2.8	3.3	3.4	4.0	3.7	4.3
63	+ 0.3	-	-	1.5	1.9	2.2	2.7	2.8	3.3	3.5	4.1	4.3	5.0		
75	+ 0.3	-	-	1.8	2.2	2.6	3.1	3.4	4.0	4.2	4.9	5.1	5.9		
90	+ 0.3	1.3	1.7	2.1	2.6	3.1	3.7	4.0	4.6	5.0	5.7	6.1	7.1		
110	+ 0.4	1.6	2.0	2.5	3.0	3.7	4.3	4.9	5.6	6.1	7.1	7.5	8.7		
125	+ 0.4	-	-	2.9	3.4	4.3	5.0	-	-	-	-	-	-		
140	+ 0.5	2.0	2.4	3.2	3.8	4.8	5.5	6.3	7.3	7.7	8.9	9.5	11.0		
160	+ 0.5	2.3	2.8	3.7	4.3	5.4	6.2	7.2	8.3	8.8	10.2	10.9	12.6		
180	+ 0.6	2.6	3.1	4.2	4.9	6.1	7.1	8.0	9.2	9.9	11.4	12.2	14.1		
200	+ 0.6	2.9	3.4	4.6	5.3	6.8	7.9	8.9	10.3	11.0	12.7	13.6	15.7		
225	+ 0.7	3.3	3.9	5.2	6.0	7.6	8.8	10.0	11.5	12.4	14.3	15.3	17.6		
250	+ 0.8	3.6	4.2	5.7	6.5	8.5	9.8	11.2	12.9	13.8	15.9	17.0	19.6		
280	+ 0.9	4.1	4.8	6.4	7.4	9.5	11.0	12.5	14.4	15.4	17.8	-	-		
315	+ 1.0	4.6	5.3	7.2	8.3	10.7	12.4	14.0	16.1	17.3	19.9	-	-		
355	+ 1.1	5.1	5.9	8.1	9.4	12.0	13.8	15.8	18.2	-	-	-	-		
400	+ 1.2	5.8	6.7	9.1	10.5	13.5	15.6	-	-	-	-	-	-		
450	+ 1.4	6.5	7.5	10.3	11.9	15.2	17.5	-	-	-	-	-	-		

**Note:** 1) Pipes are offered in light grey (LG) and/or dark grey (DG) colours and in standard lengths of 6 m. Pipes are offered both in plain and socketed form, based on diameter and class of pipe. 2) Ringtight pipes with integral rubber ring socket (Elastomeric joint) are available from 63 mm to 315 mm in 4, 6 and 10 kgf/cm<sup>2</sup> pressure class. 3) If desired pipes of non standard wall thickness, lengths and colour can also be offered. 4) Prefix "PN" indicates Nominal Pressure, i.e., working pressure.

	Size in mm	Available Pressure Rating in kgf /cm <sup>2</sup> (PN)
	20	10, 16
	25	10, 16
	32	10, 16
	40	6, 10
	50	3, 6, 10, 16
	63	1, 6, 10, 16
	75	1, 6, 10, 16
	90	1, 6, 10, 16
	110	1, 6, 10, 16
	140	3, 6
	160	6, 10
	200	6
	250	6


**Coupler**

Application/Special note: These are used for joining of two uPVC pipes. Fabricated couplers are also available in 20 to 400 mm sizes in different pressure class.


	Size in mm	Available Pressure Rating in kgf /cm <sup>2</sup> (PN)
	20	3, 10, 16
	25	3, 10, 12.5, 16
	32	3, 10, 16
	40	3, 6, 10, 16
	50	3, 4, 6, 10, 16
	63	1, 2, 3, 4, 6, 10, 16
	75	1, 2, 3, 4, 6, 10, 16
	90	1, 2, 3, 4, 6, 10, 16
	110	1, 2, 3, 4, 6, 10, 16
	140	4, 6
	160	*3, 4, 6, 10
	180	6
	200	4, 6
	250	6
	315	4

**Elbow 90°**


Application/Special note: These are used for short turns of 90°. These are not advisable on large pipeline involving high pressure.

	Size in mm	Available Pressure Rating in kgf /cm <sup>2</sup> (PN)
	20	16
	25	16
	32	16
	40	6, 16
	50	6, 16
	63	6, 16
	75	6, 16
	90	6, 16
	110	4, 6, 16
	140	4
	160	4, 6
200	4, 6	
250	6	

**Elbow 45°**


	Size in mm	Available Pressure Rating in kgf /cm <sup>2</sup> (PN)
	32 x 25	10
	75 x 63	6
	90 x 50	6
	90 x 63	6
	90 x 75	6
	110 x 63	6
	110 x 75	6
110 x 90	6	

**Reducing Elbow**


	Size in mm	Available Pressure Rating in kgf /cm <sup>2</sup> (PN)
	20 x 15 (1/2")	10
	25 x 15 (1/2")	10
	25 x 20 (3/4")	10
	*32 x 15 (1/2")	10
	50 x 40 (1 1/2")	16
	63 x 50 (2")	6, 16
	75 x 50 (2")	6
	75 x 65 (2 1/2")	6
	90 x 80 (3")	6
	110 x 100 (4")	6

**Elbow 90°**  
One side threaded


Application/Special note: These are used for short turns of 90°. These are not advisable on large pipe lines.

	Size in mm	Available Pressure Rating in kgf /cm <sup>2</sup> (PN)
	75 (2 1/2")	10
	90 (3")	10

**Elbow 90°**  
Both side Threaded


	Size in mm	Available Pressure Rating in kgf /cm <sup>2</sup> (PN)
	20 x 15 (1/2")	10
	25 x 15 (1/2")	10
	25 x 20 (3/4")	10
	*32 x 15 (1/2")	10
	63 x 50 (2")	6
	75 x 65 (2 1/2")	6
	90 x 80 (3")	6
	110 x 50 (2")	6
	110 x 65 (2 1/2")	6
	110 x 80 (3")	6
110 x 100 (4")	6	

**One Side Threaded Tee**

	Size in mm	Available Pressure Rating in kgf /cm <sup>2</sup> (PN)
	20	3, 10, 16
	25	3, 10, 16
	32	3, 10, 16
	40	3, 6, 10, 16
	50	3, 4, 6, 10, 16
	63	1, 2, 3, 4, 6, 10, 16
	75	1, 2, 3, 4, 6, 10, 16
	90	1, 2, 3, 4, 6, 10, 16
	110	1, 2, 3, 4, 6, 10, 16
	140	4, 6
	160	*3, 4, 6, 10
	180	6
	200	4, 6
	250	6
	315	4

**Equal Tee**









Application/Special note: These are used for bypass and taking equal size service line out of main line at 90°.

	Size in mm	Available Pressure Rating in kgf /cm <sup>2</sup> (PN)
	25 x 20	10
	32 x 20	10
	32 x 25	10
	40 x 20	6
	40 x 25	10
	50 x 25	10
	50 x 32	6
	63 x 25	10
	63 x 32	10
	63 x 40	6
	63 x 50	6, 10
	75 x 40	6
	75 x 50	6
	75 x 63	4, 6
	90 x 63	4, 6
	90 x 75	4, 6
	110 x 50	6
	110 x 63	6
	110 x 75	4, 6
	110 x 90	4, 6
140 x 110	6	
160 x 75	4	
160 x 110	4, 6	
200 x 110	6	
200 x 160	6	

**Reducing Tee**

Application/Special note: These are used for by pass and taking lower diameter service line out of main line.

**Note :** 1) Fittings are offered in Light Grey (LG) and Dark Grey (DG) colour. All the fittings shown in dark grey colour are in 16kgf/cm<sup>2</sup> (PN) pressure class. 2) Prefix "PN" indicates nominal Pressure i.e. working pressure. 3) \*Marked fittings will be shortly introduced.

	Size in mm	Available Pressure Rating in kgf /cm <sup>2</sup> (PN)
	63 x 75	6
<b>Enlarging Tee</b>	Application/Special note : These are used for by pass and taking higher diameter service line out of main line.	
	63 75 90 110	6 6 6 6
<b>Cross Tee</b>	Application/Special note : These are used for by pass and taking equal size service line on both side of main line.	
	40x20 63x20 63x25 63x32 *63x40 75x25	6 4 4 4 6 4
<b>Reducing Cross Tee</b>		
 	20 25 32 40 50 63 75 90 110 140 160	10, 16 10, 16 10, 16 6, 16 6, 16 6, 10, 16 6, 10, 16 6, 10, 16 6, 10, 16 6 6
<b>Male Threaded Adaptor (M.T.A.)</b>	Application/Special note : These are used to connect a uPVC pipeline directly to a female threaded metal pipe and all types of valves, taps, pumps etc. through a male portion.	
	75 x 50 (2") 90 x 50 (2") 90 x 65 (2½")	6 6 6
<b>Reducing Male Threaded Adaptor (R.M.T.A.)</b>	Application/Special note : These are used to connect a uPVC pipeline directly to a female threaded metal pipe.	
 	20 25 32 40 50 63 75 90 110 160	3, 10, 16 10, 16 10, 16 6, 16 6, 16 6, 10, 16 6, 10, 16 6, 10, 16 6, 10, 16 6
<b>Female Threaded Adaptor (F.T.A.)</b>	Application/Special note : These are used to connect a uPVC pipeline directly to a male threaded metal pipe.	

Size in mm	Available Pressure Rating in kgf /cm <sup>2</sup> (PN)
25 x 15 (½")	10, 16
32 x 15 (½")	10, 16
32 x 20 (¾")	10
40 x 25 (1")	6
50 x 32 (1¼")	6
63 x 40 (1½")	6
75 x 50 (2")	6
90 x 50 (2")	6
90 x 65 (2½")	6
110 x 50 (2")	6
110 x 80 (3")	6
Application/Special note : These are used to connect a uPVC pipeline directly to a metal pipe of over diameter or vice-versa.	
25 x 20	10
32 x 20	10
32 x 25	10, 16
40 x 25	6
40 x 32	6, 16
50 x 25	6
50 x 32	6
50 x 40	6, 16
63 x 32	6
63 x 40	6
63 x 50	6, 16
75 x 40	6
75 x 50	6
75 x 63	6
90 x 50	6
90 x 63	6
90 x 75	6
110 x 50	6
110 x 63	6
110 x 75	6
110 x 90	6
140 x 75	4
140 x 90	4
140 x 110	4, 6
160 x 90	4
160 x 110	4, 6
160 x 140	4
180 x 110	6
200 x 110	4, 6
200 x 160	4, 6
200 x 180	6
250 x 200	6
Application/Special note : These are used to convert the service line into small or extra small lines.	
25 x 20	10
32 x 20	10, 16
32 x 25	10, 16
40 x 25	16
40 x 32	6, 16
50 x 25	16
50 x 32	6
50 x 40	6, 16
63 x 32	16
63 x 40	6
63 x 50	6, 16
75 x 40	6
75 x 50	6, 16
75 x 63	6, 16
90 x 50	6
90 x 63	6
90 x 75	6, 16
110 x 63	6



**Reducing Female Threaded Adaptor (R.F.T.A.)**




**Reducer**





**Reducing Bush**

**Note :** 1) Fittings are offered in Light Grey (LG) and Dark Grey (DG) colour. All the fittings shown in dark grey colour are in 16kgf/cm<sup>2</sup> (PN) pressure class. 2) Prefix "PN" indicates nominal Pressure i.e. working pressure. 3) \*Marked fittings will be shortly introduced.


	Size in mm	Available Pressure Rating in kgf /cm <sup>2</sup> (PN)
	<b>Reducing Bush</b>	110 x 75
	110 x 90	6, 16
	140 x 75	6
	140 x 90	6
	140 x 110	6
	160 x 90	6
	160 x 110	6
	200 x 160	6
	250 x 160	6
	250 x 200	6

Application/Special note : These are used along with Coupler, Elbow, Tee, MTA, FTA to convert service line or fitting to smaller line.


	Size in mm	Available Pressure Rating in kgf /cm <sup>2</sup> (PN)
	<b>Threaded Reducing Bush</b>	75 x 50 (2")
	90 x 65 (2½")	6

	Size in mm	Available Pressure Rating in kgf /cm <sup>2</sup> (PN)
	<b>Tail Piece</b>	63
	75	6, 16
	90	6, 16
	110	6, 16
	140	6
	160	6, 16
	200	6, 16


Application/Special note : These are used for connecting an air release valve / water fill way valve (C.I./M.S. etc.) and any other flanged fitting (like strainer) Non-return valve, pumps etc with the pipe.

	Size in mm	Available Pressure Rating in kgf /cm <sup>2</sup> (PN)
	<b>Flange</b>	63
	75	6
	90	6
	110	6


Application/Special note : These are used along with Tail piece for connecting an air release valve, Non-return valve, pumps and metal pipes etc with the pipe.

	Size in mm	Available Pressure Rating in kgf /cm <sup>2</sup> (PN)
	<b>Flange Adapter</b>	63
	75	6
	90	6
	110	10
	160	10

Application/Special note : These are used for connecting an air release valve, Non-return valve, pumps and metal pipes etc with the pipe.

	Size in mm	Available Pressure Rating in kgf /cm <sup>2</sup> (PN)
	<b>Blind Flange</b>	63
	75	10
	90	10
	110	10

Application/Special note : These are used for to close the end of pipeline for various application.

	Size in mm	Available Pressure Rating in kgf /cm <sup>2</sup> (PN)
	<b>Service Saddle</b>	40 x 15 (½")
	50 x 15 (½")	6
	50 x 20 (¾")	6
	50 x 25 (1")	6
	63 x 15 (½")	6,10
	63 x 20 (¾")	6,10
	63 x 25 (1")	6,10
	75 x 15 (½")	6,10
	75 x 20 (¾")	6,10

Size in mm	Available Pressure Rating in kgf /cm <sup>2</sup> (PN)
75 x 25 (1")	6,10
90 x 15 (½")	6,10
90 x 20 (¾")	6,10
90 x 25 (1")	6,10
110 x 15 (½")	6,10
110 x 20 (¾")	6,10
110 x 25 (1")	6,10
140 x 15 (½")	6
140 x 20 (¾")	6
140 x 25 (1")	6
160 x 15 (½")	6
160 x 20 (¾")	6
160 x 25 (1")	6
200 x 25 (1")	6
200 x 32 (1¼")	6
200 x 40 (1½")	6
200 x 50 (2")	6

Application/Special note : These are used for taping the large service main line into small feeder line for house hold purpose and for connecting air release valves.



**Service Saddle**

Size in mm	Available Pressure Rating in kgf /cm <sup>2</sup> (PN)
20	10
25	10
32	10
40	6
50	6
63	4, 6
75	4, 6
90	4, 6
110	4, 6
140	4
160	6
180	4, 6
200	6
250	6
315	6

Application/Special note : These are used to close the end of pipe line.



**End Cap (Plain)**

Size in mm	Available Pressure Rating in kgf /cm <sup>2</sup> (PN)
20 x 15 (½")	10
25 x 20 (¾")	10
32 x 25 (1")	10
40 x 32 (1¼")	6
50 x 40 (1½")	6
63 x 50 (2")	6
75 x 65 (2½")	6
90 x 80 (3")	6
110 x 100 (4")	6
140 x 125 (5")	6

Application/Special note : Threaded end cap with inside threads (BSP threads) are used to close the end of pipe line. Note : In case of threaded fittings avoid overtightening the joint with wrench as it may damage the uPVC threads.



**End Cap (Threaded)**

Size in mm	Available Pressure Rating in kgf /cm <sup>2</sup> (PN)
63	6
75	6
90	6
110	6
140	6
160	6
200	6
250	4








Application/Special note : These are used for by pass and taking equal size service line out of main line at 45°



**Single Y**

**Note :** 1) Fittings are offered in Light Grey (LG) and Dark Grey (DG) colour. All the fittings shown in dark grey colour are in 16kgf/cm<sup>2</sup> (PN) pressure class. 2) Prefix "PN" indicates nominal Pressure i.e. working pressure. 3) \*Marked fittings will be shortly introduced.

	Size in mm	Available Pressure Rating in kgf /cm <sup>2</sup> (PN)
 <b>Reducing Y</b>	110 x 63 160 x 110 200 x 110 200 x 160	6 6 4 4
 <b>Female Threaded Tee</b>	25 x 15 (1/2") 32 x 15 (1/2")	10, 16 10
 <b>Female Threaded Elbow</b>	25 x 15 (1/2") 32 x 15 (1/2")	10, 16 10
 <b>Female Threaded Joint</b>	25 x 15 (1/2") 32 x 15 (1/2")	16 10
 <b>Male Threaded Joint</b>	25 x 15 (1/2") 25 x 20 (3/4")	10 16
 <b>Ball Valve</b>	25 32 40 50 63	16 16 16 16 16
 <b>Ball Valve</b>	75 90 110	10 10 10
 <b>Threaded Ball Valve (Union Type)</b>	25 (3/4")	16
 <b>Non Return Valve (NRV)</b>	63 75 90 110	16 10 10 10

Size in mm	Available Pressure Rating in kgf /cm <sup>2</sup> (PN)	
3/4" 1" 1 1/4" 1 1/2" 2"	10 10 10 10 10	 <b>Air Release Valve</b>
75 90 110 *160	10 10 10 10	 <b>Butterfly Valve</b>
25 32 40 50 63	10 10 10 10 10	 <b>Union</b>
*25 32 *40 50 63 *75 *90	10 10 6 6 6 6 6	 <b>Bend</b>
63 75 90 110 140 160 180 200	6 6 6 6 6 6 6 6	 <b>Leakage Coupler (F)</b>
63 75 90 110 140 160 180 200 225 250 280 315	6, 10 4, 6, 10 4, 6, 10 4, 6, 10 4, 6, 10 4, 6, 10 4, 6, 10 4, 6, 10 4, 6, 10 4, 6, 10 4, 6, 10 4, 6, 10	 <b>Repair Coupler Long (with elastomeric rubber seal)</b>
63 75 90 110 140 160 180 200 225 250 280	10 10 10 10 10 10 10 10 10 10 10	 <b>Repair Coupler (F)</b>

Special note : All the leakage couplers are available in 6", 9" and 12" standard length.

Note: 63 to 160 mm Repair Coupler Short (with elastomeric rubber seal) is also made available in 4 & 6 kgf/cm<sup>2</sup>.

**Note :** 1) Fittings are offered in Light Grey (LG) and Dark Grey (DG) colour. All the fittings shown in dark grey colour are in 16kgf/cm<sup>2</sup> (PN) pressure class. 2) Prefix "PN" indicates nominal Pressure i.e. working pressure. 3) \*Marked fittings will be shortly introduced. • All the dimensions unless otherwise specified are in mm



**Solvent Cement**

Size	Box qty
50 ml	100
100 ml	50
250 ml	80
500 ml	50
1000 ml	24
5000 ml	4

Note : Recommended for smaller sizes and lower pressure class, upto 75 mm size - any pressure class, upto 110 mm size in 4 and 6 kgf/cm<sup>2</sup>, upto 200 mm size - 2.5 kgf/cm<sup>2</sup>



**Solvent Cement Heavy Duty**

1000 ml
5000 ml

Note : Recommended for larger sizes and higher pressure class, 90mm and 110mm in 10 and 12.5 kgf/cm<sup>2</sup>, 140mm and above sizes in 4,6,10 and 12.5 kgf/cm<sup>2</sup>

Size in mm
110-175x15 (1/2")
110-175x20 (3/4")
110-175x40 (1 1/2")
200-300x40 (1 1/2")
200-300x50 (2")
300-400x50 (2")



**Strap Saddle**

**Handmade Fittings:** Besides a vast range of moulded fittings, an exhaustive range of handmade fitting is also available from Supreme. This range of products includes couplers, bends, short bends, tee's, reducing tee's, cross tee's, tail pieces, reducers, single or reducing Y's, end caps, leakage couplers etc. in 20 to 450 mm sizes in different pressure classes.

Handmade division of the Company is equipped to make any tailor-made product as per customer requirements. This implies a complete system solution made of the same material eliminating the dependence of the customer on any other conventional product.

**Handling Instructions:** Pipes should be kept on an even surface while storing. They should be properly supported and should not be stacked for more than 1.5 m height for a long duration.

While laying big pipelines, provision should be made for expansion of joints, air venting and proper anchorage.

**Pipes or fittings should not be cleaned with solvent cement.** Quality of solvent cement plays an important role. It is, therefore, recommended that good quality solvent cement be used.

For large diameter and higher class pipes (6 Kgf/cm<sup>2</sup> and above), always use heavy duty solvent cement. Very old, hard, semi-fluid solvent cement should not be used.




Installation of Supreme pipeline in the field

**Consumption of Solvent Cement:**

Diameter of pipe (mm)	20	25	32	40	50	63	75	90	110	140	160	180	200	225	250	280	315	355	400	450
Approx no of joints which can be made per litre of solvent cement	354	270	225	180	130	125	103	79	54	36	27	25	15	12	9	7	5	3	2	2



**Jointing Instructions:**



Cut the pipe as square as possible. Ensure that fitting of the pipe with socket of fitting is correct.



Total length of socket should be marked on pipe. In most cases, the pipe inserted should be up to the marked line and in no case should it be less than 2/3<sup>rd</sup> of pipe end.

The pipe and the socket should be clean and dry. Dust, oil, water, grease etc. should be wiped off with dry cloth or a cleaner from the surfaces to be coated with solvent cement




Roughen the outer surface of the pipe and the inner surface of the socket using sand paper or piece of hacksaw blade up to the entry mark. Stir solvent cement thoroughly.

Apply a thick coat of solvent cement using a flat clean brush evenly on the inner surface of the socket for full length of insertion and then on the outer surface of the pipe end up to the marked line.



After application of solvent cement, insert the pipe within one minute of application into the socket. Hold the joint for a few seconds and ensure that the pipe does not come out the fitting. Wipe off extra cement. Let it dry. Within 24 hours, your Supreme rigid PVC pipes are ready for use.




In case of big pipeline projects, it is recommended to refer to our installation guide.

# Ringtight Rigid PVC Pipes with Sealing Rings

## Ringtight Advantages:


These pipes are specially designed and suitable to overcome difficulties experienced while jointing higher diameter pipes using solvent cement and offer the following advantages:-

- As elastomeric sealing rings are used, requirements and precautions associated with quality and quantity of solvent cement are eliminated.
- Unlike solvent type joints, curing period is not required which allows the pipelines to be tested and brought in use immediately after jointing.
- Pipe laying and jointing is very easy, quicker and more reliable. Pipes up to 140 mm size can be jointed by hand but large diameter pipes require a jack.
- Joints are stable, watertight and can resist loads from horizontal and vertical tractive forces.
- Joints can accommodate angular deflection up to 2° and axial displacement resulting from thermal expansion and contraction which eliminates the need of expansion joints as required in solvent type joints.
- Joints can be made in any climatic condition.



## About Elastomeric Sealing Ring:

Unique design of sealing ring supplied with the pipe is made from high quality EPDM rubber to meet the practical requirements of sites, which add to installation efficiency. This seal can be safely and easily fitted in wet, cold and muddy conditions. These sealing rings offer the following advantages:-



- Very low assembling force is required for joint.
- It has large operational life (minimum life is about 50 years).
- These rings give greater reliability and joint tightness and can withstand pressures beyond that of specified testing pressure of the pipes.
- Specially suitable for underground applications.
- It is resistant to salt water, organic vegetable oils, dilute acids and alkalis normally found in waste water. It is also resistant to ultra violet radiations, bacteria, fungus and termites. In short, Supreme ringtight pipes are designed to give long term satisfaction to the customers.




## Jointing Instructions:

1. Clean the inside of the socket. Remove all traces of mud, dirt, grease, gravel and clean the elastomeric sealing ring.
2. Shape the ring into a heart shape by pinching a portion of ring from inside. Insert it into the socket and release to seat it into the groove.
3. Factory supplied pipes are provided with a 15° chamfer. Mark the insertion depth on spigot of pipe. Clean and apply lubricant to the pipe insertion depth before pushing it into the socket.
4. If pipe needs to be cut, it should be cut perpendicular to the axis of the pipe after which it should be chamfered properly.
5. Align the socket and spigot correctly in the horizontal and

vertical planes. Before insertion, ensure that no sand or dirt adheres to the lubricated surface of the pipe. Care should be taken that the spigot end is inserted in the socket at the correct angle.

6. Push the spigot into the socket until it reaches the depth of entry mark. Do not over insert. This must be done manually. Use a steel crow bar, if necessary. Protect the pipe with a wooden block. Insertion of spigot end inside the socket should be at the correct angle.
7. In case of large diameter pipes, if the crow bar does not give sufficient leverage, use of a jointing jack may be helpful.



• Any specification may change without prior notice. • All information contained in this literature is given in good faith and believed to be accurate and reliable. Because of many factors which may be outside our knowledge or control and affect the use of the product, no warranty is given or implied with respect to such information, nor do we offer any warranty of immunity against patent infringement. No responsibility can be accepted for any error, omissions or incorrect assumptions.

## The Supreme Industries Ltd. (Plastic Piping Division)

**Corporate Office** : 1161/1162, Solitair Corporate Park, Building No. 11,167, Guru Hargovindji Marg, Chakala, Andheri Ghatkopar Link Road, Andheri (East) Mumbai - 400 093. India. Tel: 91-22-67710000, 40430000 Fax: 67710099 /40430099.

**Regd. Office** : 612 Raheja Chambers, Nariman Point, Mumbai 400 021. India Tel.: (022) 22851656, 22820072 Fax : (91-22) 22851657

**E-mail**: pvc-pipes@supreme.co.in **Website** : www.supreme.co.in

**Works** : • D-101/102, MIDC, Jalgaon - 425 003.

• Unit No.3, Gat No.47-48, at post Gadegaon, Tal. Jamner, Dist., Jalgaon- 425 114

**Export Division** : 91-22-6771 0126 / 4043 0126 Fax : 6771 0130

**Overseas Office** : Sharjah, U.A.E. Tel # + 971 6 557 4484; Fax # + 971 6 557 4485

CIN: L35920MH1942PLC003554

## Branch Offices Tel.

<b>Ahmedabad</b>	: 079-30028371
<b>Bangalore</b>	: 080-30913715
<b>Chennai</b>	: 044-39811182
<b>Cochin</b>	: 0484-2385346
<b>Hyderabad</b>	: 040-23221130
<b>Indore</b>	: 0731-2432684
<b>Jaipur</b>	: 09910995853
<b>Jalgaon</b> Gadegaon	: 0257-3050541,42
<b>Kanpur</b>	: 0512-2332280
<b>Kolkata</b>	: 033-30070123
<b>Noida (Delhi)</b>	: 0120-6660000

Authorised Distributor



I & T SIL Gadegaon, Dist-Jalgaon • PC/AG/MKG/01 • REV.16-08/2017